CONSTRUCTION SPECIFICATIONS

CONTRACTOR_	
_	
-	
Specification sheet	for
-	Lot
Garage – Carport _	Drive
Porches	Patio/Deck
SLAB:	Fill sand to grade
	Chain walls- per prevailing code usually 16" x 24"
	Slab 4" 300 PSI concrete
	6 mill vapor barrier
	6" x 6" 6 ga. wire mesh
	5/8" rebar in chain walls
	Certification of termite treatment
FRAME:	2" x 4" pressure treated bottom plated
	Double 2" x 4" top plated
	Studs on 16" centers
	Ceiling joist on 16" centers thickness according to span "code"
	Rafters on 24" center usually 2" x 6"
	•
	5/8" plywood sheeting on roof
	15 lbs felt – composition shingles type & color
	Metal
	Wind turbin roof vents
EXTERIOR	½" plywood on walls under vinyl
FINISH:	3/4' foil Styrofoam on walls behind brick
	Barricade house wrap over sheeting & foil
	Type of siding and color
	Brick type & allowance
	Window. Type
	Exterior door units. Type & allowance
	Soffits Facia
PLUMBING:	Per prevailing code-water lines copper tubing
	Sewer-PVC or cast iron
	Tubs- Type & allowance
	Faucets- Type & allowance
	••
	Sink- Type & allowance Lavatories
	Lavaiones

ELECTRICIAL:	Per prevailing code – all copper wire – G.E. breakers
	Receptacles & switches per plan
	Lighting & fan allowance
AIR & HEAT:	Type unit & size
	Attic
INSULATION:	Walls – type of batt & size
	Ceiling
	Wall paper - allowance
	Paneling
	Cabinets
	Counter tops kitchen
	Baths
	Interior doors
	Molding
	Floor coverings & allowance
	Hardware
	Appliances & allowances
	Misc.
Bid Price \$	
	Contractor